

OSCILLATOR SBXO - 19

APPLICATIONS

STANDBY FUNCTION OSC.

7mm X 5mm X 1.8mm(H)

PICTURE
AREA

- ▶ Mobile system
- ▶ Portable equipment
- ▶ Notebook
- ▶ PDA

OUTLINE DIMENSIONS

Pin No.	Function
1	Standby function
2	GND
3	Frequency output
4	Vcc

< PAD LAYOUT >

ELECTRICAL SPECIFICATIONS

Frequency range	1.000MHz to 80.000MHz		
Frequency stability	±25ppm	±50ppm	±100ppm
	Inclusive of operating temperature		
Operating temperature range	0 °C ~ 70 °C		
Storage temperature range	-50 °C ~ 105 °C		
Input voltage	+1.8Vdc ±0.2V		
Input current	15mA max. (at 80.000MHz)		
"0" / "1" level	+0.3V max. / +1.5V min.		
Duty ratio	55/45% or 45/55% (typical)		
Standby current	100uA max.		
Standby function (Pin #1)	High (or Open) = Active (Normal operation)		
	Low = Hi-impedance (Stop oscillation)		
Rise & Fall time	5nS max.		
Start up time	10mS max.		
Fan out	15pF		
Aging (at 25 °C)	±5ppm / year max.		

ENVIRONMENTAL & MECHANICAL SPECIFICATIONS

Shock	MIL-STD-883C, Method 2002, Condition B
Vibration	MIL-STD-883C, Method 2007, Condition A
Solderability	MIL-STD-883C, Method 2003
Seal integrity	MIL-STD-883C, Method 1014, Condition C & A2
Marking	MIL-STD-202F, Method 215

PART NUMBERING GUIDE

S B X O 1 9 B A

- Sbtron
- Oscillator
- Model No.

Temperature range

- A = 0 °C ~ 70 °C
- B = -20 °C ~ 70 °C
- C = -30 °C ~ 80 °C
- D = Customize

Frequency stability

- A = ± 25 ppm
- B = ± 50 ppm
- C = ±100 ppm
- D = Customize

*Standard specifications for product indicated in BLUE character
Specifications subjects to change without notice & If you need other specifications, Contact our factory.*

